

Počet stupňů	Měrná energie			Dopravní výška			Motor TU-85	Světln. výtlaku	Průměr soustr.	Prům. vrtu	Délka soustr.	Hmotn. soustr.	Kabel		Nast. jističe							
													do 50m	nad50m do100m								
	Y (J/kg)			H (m)			kW	DN (mm)	mm	mm	mm	kg	4x mm2	4x mm2	A							
Objemový Průtok Q (l/s)	1,3	1,66	2	1,3	1,66	2	Typ čerpadla U VN 1															
Poč. stupňů																						
4	441	392	333	45	40	34	3,0	G 1 1/2" (40)	185	ČSN 75 5115	1074	75	1,5	1,5	5,0							
5	559	490	412	57	50	42					1147	83			5,3							
6	669	588	490	68	60	50					1185	85			5,8							
7	775	676	549	79	69	56					1223	87			6,2							
8	853	745	617	87	76	63	5,5				G 1 1/2" (40)	185	ČSN 75 5115	1261	89	2,5	2,5	6,6				
9	961	853	735	98	87	75								1299	91			7,3				
10	1039	941	804	106	96	82								1337	93			7,9				
11	1137	1029	882	116	105	90								1511	115			9,0				
12	1235	1127	961	126	115	98								1549	117			9,5				
13	1343	1226	1039	137	125	106								1587	119			10,0				
14	1451	1314	1127	148	134	115								1625	121	11,0						
15	1559	1412	1206	159	144	133								1663	123	12,0						
Objemový průtok Q (l/s)	2,5	3,3	4,2	2,5	3,3	4,2								Typ čerpadla A UBA 2A								
Poč. stupňů																						
2	353	314	235	36	32	24	3,0	G 3" (80)	197	ČSN 75 5115	1175	98	1,5	2,5	6,5							
3	510	441	333	52	45	34	5,5				G 3" (80)	197	ČSN 75 5115	1285	105	2,5	4,0	8,0				
4	725	637	400	74	65	41								1285	107			13,5				
5	912	784	627	93	80	64								1395	115			14,0				
6	1118	980	784	114	100	80								1435	122			17,0				
7	1294	1145	912	132	117	93	11,0				G 3" (80)	197	ČSN 75 5115	1585	138	4,0	6,0	20,0				
8	1490	1304	1039	152	133	106								1585	139			22,0				
9	1677	1471	1176	171	150	120								1695	148			24,0				
10	1853	1628	1314	189	166	134								1765	162			27,0				
Objemový průtok Q (l/s)	4,1	5,8	7,5	4,1	5,8	7,5	Typ čerpadla U BG 1															
Poč. stupňů																						
2	294	264	206	30	27	21	5,5				G 3" (80)	205	ČSN 75 5115	1248	98	1,5	2,5	7,0				
3	441	392	314	45	40	32		1348	109	11,0												
4	588	500	382	60	51	39		1448	118	13,0												
5	745	647	500	76	66	51		1588	132	15,0												
6	902	784	617	92	80	63	11,0	G 3" (80)	205	ČSN 75 5115				1728	148	2,5	4,0	18,5				
7	1039	902	716	106	92	73								1828	157			24,0				
8	1196	1044	823	122	106	84								1928	165			26,0				
9	1353	1176	921	138	120	94								2098	187			28,0				
10	1500	1304	1020	153	133	104	2198	196	30,0													
Objemový průtok Q (l/s)	8,3	11,7	15	8,3	11,7	15	Typ čerpadla U BX 1															
Poč. stupňů																						
2	235	196	147	24	20	15	5,5	G 3" (80)	208	ČSN 75 5115				1322	108	1,5	2,5	10,0				
3	333	264	176	34	27	18	7,5				1502	126	14,0									
4	461	372	245	47	38	25	11,0				G 3" (80)	208	ČSN 75 5115	1682	146	2,5	4,0	19,0				
5	559	451	304	57	46	31								1822	158	24,0						
6	657	539	372	67	55	38								2032	183	26,0						
7	765	627	431	78	64	44	15,0				2172	196	6,0	10,0	30,0							